


Gabel-Kabelschuh unisoliert und Sonderausführung

Temperaturbereich: bis +125°C



Solderless Spade Terminals non-insulated

mm ² (AWG)	Bestell-Type	Norm	– Dimensionen in mm –							Werkzeug Tool
			s	d ₁	d ₂	d ₃	l ₁	l ₂	a	
0,3 – 0,75 (24-20)	GKS-0832		0,5	3,2	5,5	1,4	12,0	9,6	4,5	T 50 T 53 DKB-0325 GWB-4099 PWZ-2000D-1322
	GKS-0837			3,7	7,5		15,5	11,6		
	GKS-0843			4,3	7,5		15,5	11,6		
	GKS-0853			5,3	9,0		16,0	11,6		
0,5 – 1,5 (20-16)	GKK-1532	UL CSA	0,8	3,2	5,5	1,7	14,0	11,0	5,0	
	GKL-1532			3,2	5,8		16,0	11,0		
	GKL-1537			3,7	5,8		14,0	11,0		
	GKS-1543			4,3	7,0		16,5	12,5		
	GKS-1553			5,3	9,6		17,5	12,8		
	GKS-1565			6,5	11,0		20,0	13,1		
1,1 – 2,6 (16-14)	GKK-2532	UL CSA	0,8	3,2	5,5	2,3	14,0	12,0	5,0	
	GKL-2532			3,2	5,9		16,0	11,1		
	GKL-2537			3,7	6,4		16,0	11,1		
	GKL-2543			4,3	7,0		16,0	11,5		
	GKS-2553			5,3	8,0		16,0	11,6		
	GKS-2565			6,5	12,0		20,0	13,1		
2,7 – 6,0 (12-10)	GKN-4643	UL	1,0	4,3	7,9	3,6	18,2	14,1	6,5	
	GKS-4653			5,3	9,0		18,2	14,1		
	GKS-4665			6,5	11,0		20,2	15,0		
	GKS-4685			8,5	14,0		23,5	19,0		
6 – 10 (8)	GKS-1043		1,2	4,5	10,5	4,6	22,4	17,5	8,5	GWB-4099 PWZ-2000D-1516
	GKS-1053			5,3	10,5					
	GKS-1065			6,5	11,0					
10 – 16 (6)	GKS-1653		1,2	5,3	11,0	5,8	26,0	21,0	10,0	
	GKS-1665			6,5	11,0					
	GKS-1685			8,5	13,8					

Material: Elektrolytkupfer, galvanisch verzinkt, hartverlötet, RoHS konform

Charakteristik: Rillenprägung im Hülsenbereich

Maßänderungen im Sinne des technischen Fortschritts vorbehalten.

Presswerkzeuge: Seite xxx