

Ring-Kabelschuh DIN 46237


und Sonderausführung

Isolation: Polyamid (PA)

Temperaturbereich: -40°C bis +105°C

Belastbarkeit: max. 600V

6A 16A 25A 48A



Solderless Terminals pre insulated PA

Kennfarbe	mm ² (AWG)	Bestell-Type	Norm	- Dimensionen in mm -								Werkzeug Tool
				s	d ₁	d ₂	d ₃	d ₄	l ₁	l ₂	a	
Yellow	0,1 – 0,5 (26-20)	RKSN-0522	UL	0,5	2,2	5,4	1,0	2,3	16	13,5	3,5	DSA 0115
		RKSN-0532			3,2	5,4						
		RKSN-0537			3,7	5,4						
		RKSN-0543			4,3	5,4						
		RKSN-0553			5,3	8,0						
Green	0,25 – 0,75 (22-18)	RKSN-0822	UL CSA	0,5	2,2	5,5	1,4	2,9	17,5	14,7	4,5	DSA 0115
		RKSN-0832			3,2	5,5			17,5	14,7		
		RKSN-0837			3,7	7,5			21,0	17,3		
		RKSN-0843			4,3	7,5			21,0	17,3		
		RKSN-0853			5,3	9,0			21,5	17,0		
Red	0,5 – 1,5 (20-16)	RKSN-1522	DIN LN VG UL CSA	0,8	2,2	5,5	1,7	4,1	17,5	15,0	4,5	T50 T51 T53 DSA 0115 DSA 0725 GSA 0760 GSA 0760C
		RKSN-1532			3,2	5,5			17,5	15,0		
		RKSN-1533			3,2	6,0	1,6	4,0	20,0	17,0	11,0	
		RKSN-1537			3,7	6,0			19,5	16,0		
		RKSN-1541			4,1	6,8	19,5	16,0				
		RKSN-1543			4,3	8,0	21,5	17,0				
		RKSN-1551			5,1	8,0	1,7	4,1	21,1	17,0	4,5	
		RKSN-1553			5,3	10,0			23,5	18,5		
		RKSN-1565			6,5	12,0	25,7	19,5				
		RKSN-1585			8,5	12,0	25,7	20,0				
RKSN-1510	10,5	16,5	30,0	22,0								
Blue	1,1 – 2,6 (16-14)	RKSN-2532	DIN LN VG UL CSA	0,8	3,2	6,0	2,3	4,5	19,5	17,0	5,0	T50 T51 T53 DSA 0725 GSA 0760 GSA 0760C
		RKSN-2537			3,7	6,0			19,5	17,0		
		RKSN-2541			4,1	6,6			19,9	16,6		
		RKSN-2543			4,3	8,0			21,3	18,0		
		RKSN-2551			5,1	8,0			21,5	17,5		
		RKSN-2553			5,3	10,0			25,0	20,0		
		RKSN-2565			6,5	11,0			27,0	22,0		
		RKSN-2585			8,5	14,0			29,5	23,0		
		RKSN-2510			10,5	15,0			30,0	22,5		
		RKSN-2513			13,0	19,0			34,0	24,5		
Yellow	2,7 – 6,0 (12-10)	RKSN-4643	DIN LN VG UL CSA	1,0	4,3	8,0	3,6	6,8	24,5	21,0	6,0	T50 T51 T53 GSA 0760 GSA 0760C
		RKSN-4651			5,1	9,0			25,7	21,2		
		RKSN-4653			5,3	10,0			26,8	22,0		
		RKSN-4665			6,5	11,0			28,0	23,0		
		RKSN-4685			8,5	14,0			32,5	26,0		
		RKSN-4610			10,5	15,0			35,5	28,0		
		RKSN-4613			13,0	19,2			40,0	30,4		

Material: Elektrolyt-Kupfer, hartgelötet, galvanisch verzinkt, RoHS konform

Charakteristik: EASY-ENTRY. Isolation aufgeweitet, halogenfrei

Maßänderungen im Sinne des technischen Fortschritts vorbehalten.

Presswerkzeuge: Seite xxx